



XF2/3-W EVOFLOW WINE

2 modules ROMFIL EVOFLUX each 10 m²
(product-dependent)

Length: 1.300 mm
Width: 800 mm
Height: 1.800 mm
Weight: 200 kg
Installed electrical power: 2,05 kW

The **ROMFIL** wine filtration system **XF2/3-W** is completely in stainless steel pipes and handmade. It has standard touch panel, pre-filter, dry running protection, over- and under-pressure protection, automatic gas pressure backwash (CO₂, N₂ or air) and an adjustable dynamic filtration.

ROMFIL crossflow filtration with EvoFlow Technology for wine

- No CO₂ loss
- No increase in temperature
- No loss of aroma
- No foreign flavors
- Only one sufficient filtration gear
- Reduced residual quantity losses compared to conventional wine clarification
- Economical and low-maintenance technology
- Evoflux modules durable up to 70 degrees Celsius
- Under 50 db operating noise
- With delivery directly usable because preassembled

Options (selection)

Option XF3: Extension to **XF3** - 3. Hollow fibre wine filter module with 10 m² = 30 m² Current capacity up to 3.750 l/h. Installed electrical power: 2,05 kW

Option 3/2/1: Switching to 1 module for the filtration of smaller quantities.

Option WIFI, text message, Email: The WIFI option allows customers to track and monitor operation of their Romfil Crossflow Filtration System via smartphone, tablet or PC. With the Text Message/ Email Option, the filtration system sends a text message (SMS) with the filter's status messages to a pre-set mobile phone.

Option Vario: With the Vario function, the filter decreeds of a control system for an external feeding pump. You can operate with the filter directly at the supply tank or operate indirectly through a feeding pump.

MADE IN GERMANY